




2.75W Compact Fixed Blade USB Charger PSM03A Adapter Meets EISA and ENERGY STAR Requirements



Features

- Fixed Blade
- CC & CV control
- EPS 2.0 (Efficiency Level V) *
- Low Cost
- 5 Star Standby power <0.03W
- No Y Cap

Applications

- MP3 Players
- PDA
- Personal Electronics
- Digital Cameras

Safety Approvals

- cUL/UL

Mechanical Characteristics

- Length: 58.1mm (2.29in)
- Width: 43.0mm (1.69in)
- Height: 21.0mm (0.83in)
- Weight: 80g (3oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Efficiency Level
		Min.	Max.		Line	Load	
PSM03A-050Q	5V	0A	0.55A	100mV	±5%		V

Note: (1) Measured after 10 minutes with by-pass capacitors 0.1uf // 10uf at output connector terminal.

Phihong is not responsible for any error and change. Content is subject to change without notice. Please consult the factory and visit www.phihong.com for the most up-to-date specifications.

INPUT:

AC Input Voltage Rating
100 to 240VAC

AC Input Voltage Range
90 to 264VAC

AC Input Current
0.1A(RMS) max.

Leakage Current
0.25mA max. @ 230VAC

Inrush Current (cold)
<30A for 120VAC at max. load
<60A for 240VAC at max. load
(Cold start @ ambient 25°C)

Input Power Saving
<0.15W max. @ 230VAC at no load

OUTPUT:

Efficiency
≥ 63.7% Average Efficiency
EPS 2.0

Hold-up Time
10mS min. @ 115VAC and max. load

Over-voltage Protection
8.5VDC max.

Short Circuit Protection

Output can be permanently shorted without damage when operated within specified input voltage and operating temperature ranges

ENVIRONMENTAL:

Temperature

Operation -10 to +45°C
Non-operation -40 to +85°C

Humidity (Relative Humidity Max)

Operation 10% to 90%

Immunity

ESD: EN61000-4-2. Level 3
RS: EN61000-4-3. Level 2
EFT: EN61000-4-4. Level 2
Surge: EN61000-4-5. Level 3
CS: EN61000-4-6. Level 2
Voltage Dips EN61000-4-11
Harmonic: EN61000-3-2

Emissions

FCC Part 15 Class B
EN55022 Class B
CISPR 22 Class B

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000VAC 10mA for 1 minute

DC Output Connector

USB A
D+ and D- pins shorted together inside the charger

Dimension Diagram Unit: mm

