



## 2.75W Compact Fixed Blade Charger (Europe) Ecodesign Compliant USB Adapter



### Features

- Fixed Blade
- CC & CV control
- Ecodesign ErP Directive 2009/125/EC level 2 annex 1b Compliant
- Ecodesign EU CoC Ver 5 Tier 2 Compliant
- Low Cost
- 5 Star Standby power <0.03W
- No Y Cap
- Halogen Free

### Applications

- MPEG Players
- PDA
- Personal Electronics
- Digital Camera

### Safety Approvals

- CE
- IEEE1725 Approved

### Mechanical Characteristics

- Length: 42mm (1.65in)
- Width: 43mm (1.65in)
- Height: 21.0mm (0.87in)
- Weight: 80g (3oz)

### Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Case Color
		Min.	Max.		Line	Load	
PSM03E-050Q	5V	0A	0.55A	100mV	±5%		Black
PSM03E-050Q-3W	5V	0A	0.55A	100mV	±5%		White

Note: (1) Measured after 10 minutes with by-pass capacitors 0.1uF // 10uF at output connector terminal and oscilloscope set at 20MHz.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**INPUT:****AC Input Voltage Rating**

100 to 240VAC

**AC Input Voltage Range**

90 to 264VAC

**AC Input Current**

0.1A(RMS) max.

**Leakage Current**

0.20mA max. @ 264VAC

**Inrush Current (cold)**

&lt;30A for 120VAC at max. load

&lt;60A for 240VAC at max. load

(Cold start @ ambient 25°C)

**Input Power Saving**

&lt;30mW max. @ 230VAC at no load

**OUTPUT:****Power**

2.75W Maximum

**Efficiency**

EU Coc Ver5 Tier 2

**No-Load Power Saving**

0.03W maximum at 115VAC/230VAC

**Hold-up Time**

10mS min. @ 120VAC and max. load

**Over-voltage Protection**

&gt;120%, Zener Clamp

**ENVIRONMENTAL:****Temperature**

Operation 0 to +40°C

Non-operation -25 to +85°C

Humidity 10 to 90%

**Immunity**

ESD: EN61000-4-2. Level 4

Surge: EN61000-4-5. Level 4

Harmonic: EN61000-3-2

Flicker: EN61000-3-3

**Emissions**

Complies with FCC Class B

Complies with EN55032 Class B

**Dielectric Withstand (Hi-pot) Test**

Primary to Secondary: 3000VAC

**Insulation Resistance**

Primary to Secondary: 7M ohm 500VDC

**MTBF**

200K hours minimum at 120VAC, max load

(measured at ambient 25°C)

**DC Output Connector**

USB A. D+ and D- pins shorted together

inside the charger

Dimension Diagram Unit: mm

