



DM Series



30kW Moveable DC Fast Charger

Wheels



Applications

- Parking Garages
- Commercial Fleet Operators
- EV Dealer Workshops

Features

-  Multi-Standard: CCS and CHAdeMO
-  Network or Standalone Operation
-  User Authentication
-  Supports Smart Charging and Load Balancing
-  Efficiency > 94%
-  PF > 0.99 (APFC)
-  Customization Available
-  7-inch LCD Screen with User Friendly Interface
-  IK10 (Not including screen and RFID module), IP55, NEMA 3R
-  OCPP 1.6 JSON (Upgradeable to 2.0)

Model Name		DM30 Series
Safety (Not including GB)		NRTL – cETLus (USA/Canada)
Picture		
Power Specification		
AC Input	Input Rating	3 Φ _480Vac (+10%, -15%)
	AC Input Connection	3P+N+PE (Wye configuration),TN/TT
	Max. Input Current	3 Φ 40A
	Frequency	50Hz/60Hz
	Power Factor	> 0.99
	Efficiency	>94% (at optimize V/I point)
DC Output	Output Voltage Range	CHAdEMO: 150~500Vdc/CCS:150~950Vdc
	Max. Output Current	CHAdEMO/CCS: 60A@500Vdc
	Max. Output Power	DC 30kW
	Voltage Accuracy	$\pm$ 2%
	Current Accuracy	$\pm$ 2%
User Interface & Control		
Display		7" LCD
Push Buttons		Operation Buttons / Emergency Stop Button
User Authentication		RFID: Support ISO 14443A/B, ISO 15693, FeliCa Lite-S (RCS966), OCPP, QR Code, Mobile App, & Optional Third Party Payment System
Communication		
External		Ethernet, Wi-Fi & 4G
Internal		CAN bus / RS485
Environmental		
Operating Temperature		-30°C~50°C (-22°F ~ +122°F)
Humidity		5%~95% RH, Non-Condensing
Altitude		$\leq$ 2000m (6562ft)
IP/IK Level		NEMA 3R IK10 (not including screen & RFID module)
Cooling Method		Fan Cooling
Mechanical		
Cabinet Dimension(W x D x H)		589mm x 620mm x 988mm (23.19in x 24.41in x 37.90in) cable holder 155mm (6.10in)
Weight		$\leq$ 80kg (176lbs) $\pm$ 1%
Cable Length		4m (13ft)
Protection		
Input Protection		OVP, OCP, OPP, OTP, UVP, SPD
Output Protection		OCP, SCP, OVP, LVP, OTP, IMD
Regulation		
Certification		UL 2202, UL2231, EnergyStar™
Charging Interface		CHAdEMO V1.2, DIN 70121, ISO15118, GB/T 27930