

Certificate of Compliance

Certificate Number:

UL-US-2448947-0

Report Reference:

E127643-20241215

Issue Date:

2024-12-18

Issued to:

PHIHONG TECHNOLOGY CO LTD
568 Fu Xing 3rd Rd
Guishan District Taoyuan 333611
Taiwan

This certificate confirms that representative samples of:

QQJQ - Power Supplies for Use with Audio/Video, Information and Communication Technology Equipment

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 62368-1, 3rd Ed., Issue Date: 2019-12-13, Revision Date: 2021-10-22

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



A handwritten signature in black ink that reads 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2448947-0
Report reference E127643-20241215
Date 2024-12-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
PYA18xyyyzzz, x, A, T, or W, A denotes US/Mexican plug, T denotes detachable plug, W denotes desktop model (with IEC 320 C8 inlet). yyy, 050 to 300, "yyy" are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. zzz, 001 to 370, "zzz" are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 370 represents the output current is 3.7A.	POWER ADAPTER
PYA20xyyyzzz, x, A, T, or W, A denotes US/Mexican plug, T denotes detachable plug, W denotes desktop model (with IEC 320 C8 inlet). yyy, 050 to 300, "yyy" are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. zzz, 001 to 370, "zzz" are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 370 represents the output current is 3.7A.	POWER ADAPTER
PYA24xyyyzzz, x, A, T, or W, A denotes US/Mexican plug, T denotes detachable plug, W denotes desktop model (with IEC 320 C8 inlet). yyy, 050 to 300, "yyy" are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. zzz, 001 to 370, "zzz" are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 370 represents the output current is 3.7A.	POWER ADAPTER
PYA30xyyyzzz, x, A, T, or W, A denotes US/Mexican plug, T denotes detachable plug, W denotes desktop model (with IEC 320 C8 inlet). yyy, 050 to 300, "yyy" are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents	POWER ADAPTER



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-2448947-0
Report reference E127643-20241215
Date 2024-12-18

<p>the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. zzz, 001 to 370, 'zzz' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 370 represents the output current is 3.7A.</p>	
---	--

Certificate of Compliance

Certificate Number:

UL-CA-2437114-0

Report Reference:

E127643-20241215

Issue Date:

2024-12-18

Issued to:

**PHIHONG TECHNOLOGY CO LTD
568 Fu Xing 3rd Rd
Guishan District Taoyuan 333611
Taiwan**

This certificate confirms that representative samples of:

QQJQ7 - Power Supplies for Use with Audio/Video, Information and Communication Technology Equipment Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2437114-0
Report reference E127643-20241215
Date 2024-12-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
PYA18xyyyzzz, x, A, T, or W, A denotes US/Mexican plug, T denotes detachable plug, W denotes desktop model (with IEC 320 C8 inlet). yyy, 050 to 300, "yyy" are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. zzz, 001 to 370, "zzz" are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 370 represents the output current is 3.7A.	POWER ADAPTER
PYA20xyyyzzz, x, A, T, or W, A denotes US/Mexican plug, T denotes detachable plug, W denotes desktop model (with IEC 320 C8 inlet). yyy, 050 to 300, "yyy" are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. zzz, 001 to 370, "zzz" are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 370 represents the output current is 3.7A.	POWER ADAPTER
PYA24xyyyzzz, x, A, T, or W, A denotes US/Mexican plug, T denotes detachable plug, W denotes desktop model (with IEC 320 C8 inlet). yyy, 050 to 300, "yyy" are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. zzz, 001 to 370, "zzz" are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 370 represents the output current is 3.7A.	POWER ADAPTER
PYA30xyyyzzz, x, A, T, or W, A denotes US/Mexican plug, T denotes detachable plug, W denotes desktop model (with IEC 320 C8 inlet). yyy, 050 to 300, "yyy" are 3 digits which divided by 10 is the output voltage value in V. For example, 050 represents	POWER ADAPTER



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-2437114-0
Report reference E127643-20241215
Date 2024-12-18

<p>the output voltage is 5.0Vdc, 300 represents the output voltage is 30.0Vdc. zzz, 001 to 370, 'zzz' are 3 digits which divided by 100 is the output current value in A. For example, 001 represents the output current is 0.01A, 370 represents the output current is 3.7A.</p>	
---	--



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.